

PRODUCT DETAILS

BRASS VALVE / EPDM WASHER BRASS VALVE WITH EPDM RUBBER WASHER

FULL FLOW AERATOR FULL-FLOW AERATOR FOR OPTIMUM FLOW RATE

TUBULAR FIXATION NYLON NUT WITH IMPREGNATED BRASS THREADS & COMPATIBLE STAINLESS STEEL TUBE FOR AN EASY INSTALLATION

450mm BRAIDED CONNECTORS EXTENDED MIXER BRAIDS WITH OFFSET HEX'S FOR EASIER TIGHTENING FOR EASIER INSTALLATION

EXTENDED COPPER TUBES COPPER INTERNAL TUBES ALLOW FOR EASY BRAID INSTALLATION

TECHNICAL SPECIFICATIONS

FLOW RATE 10L/MINUTE @ 50Kpa

SABS APPROVED*

BRASS GRADE DZR (dezincification resistant brass) Cz132

CHROME PLATING 200 HOUR SALT SPRAYED FINISH (Ni: 7µ & Cr: 0.2µ) THICKNESS

CLEANING INSTRUCTIONS

- 1. Avoid cleaning agents containing ingredients, such as chlorine bleach, formic acid, acetic or Hydrochloric acid.
- 2. Wipe all surfaces using a soft unabrasive cloth, with warm soapy water.



10 YEAR WARRANTY

WWW.PLUMBLINK.CO.ZA

Plumblink tries its best to ensure that the information given on our website is accurate. Although, we cannot guarantee this for certain, and accept no liability for any information.

HYDRUS SINK MIXER DECK-TYPE

031461 SPECIFICATION SHEET



