



# HYDRUS PILLAR TAP

15mm

031465

SPECIFICATION SHEET

## PRODUCT DETAILS

**BRASS VALVE / EPDM WASHER** BRASS VALVE WITH EPDM RUBBER WASHER

**FULL FLOW AERATOR** FULL-FLOW AERATOR FOR OPTIMUM FLOW RATE

**TUBULAR FIXATION** NYLON NUT WITH IMPREGNATED BRASS THREADS & COMPATIBLE STAINLESS STEEL TUBE FOR AN EASY INSTALLATION

**450mm BRAIDED CONNECTORS** EXTENDED MIXER BRAIDS WITH OFFSET HEX'S FOR EASIER TIGHTENING FOR EASIER INSTALLATION

**EXTENDED COPPER TUBES** COPPER INTERNAL TUBES ALLOW FOR EASY BRAID INSTALLATION

## TECHNICAL SPECIFICATIONS

**FLOW RATE** 12L/ MINUTE @ 50Kpa

**SABS APPROVED\***

**BRASS GRADE** DZR (dezincification resistant brass) Cz132

**CHROME PLATING** 200 HOUR SALT SPRAYED FINISH (Ni: 7µ & Cr: 0.2µ) THICKNESS

## CLEANING INSTRUCTIONS

1. Avoid cleaning agents containing ingredients, such as chlorine bleach, formic acid, acetic or Hydrochloric acid.
2. Wipe all surfaces using a soft unabrasive cloth, with warm soapy water.



**10 YEAR WARRANTY**

[WWW.PLUMBLINK.CO.ZA](http://WWW.PLUMBLINK.CO.ZA)

Plumblink tries its best to ensure that the information given on our website is accurate. Although, we cannot guarantee this for certain, and accept no liability for any information.

