



CYGNUS TALL BASIN MIXER

035577

SPECIFICATION SHEET

PRODUCT DETAILS

SEDAL CARTRIDGE SEDAL ANTI-SCALD CARTRIDGE
(TEMPERATURE CONTROL)

NEOPERL AERATOR EASY TO CLEAN AERATOR. RUN
SURFACE TO CLEAN

TUBULAR FIXATION NYLON NUT WITH IMPREGNATED
BRASS THREADS & COMPATIBLE BRASS TUBE FOR AN
EASY INSTALLATION

450mm BRAIDED CONNECTORS EXTENDED MIXER
BRAIDS WITH OFFSET HEX'S FOR EASIER TIGHTENING &
FOR AN EASIER INSTALLATION

EXTENDED COPPER TUBES COPPER INTERNAL TUBES
ALLOW FOR EASY BRAIDED INSTALLATION

TECHNICAL SPECIFICATIONS

FLOW RATE 7.8L/ MINUTE @ 300Kpa

SABS APPROVED*

BRASS GRADE DZR (dezincification resistant brass)
Cz132

CHROME PLATING 200 HOUR SALT SPRAYED FINISH
(Ni: 7 μ & Cr: 0.2 μ) THICKNESS

QUIET-FLOW TECHNOLOGY BUILT-IN NOISE
SURPRESSOR IN CARTRIDGE

CLEANING INSTRUCTIONS

1. Avoid cleaning agents containing ingredients, such as chlorine bleach, formic acid, acetic or Hydrochloric acid.
2. Wipe all surfaces using a soft unabrasive cloth, with warm soapy water.



10 YEAR WARRANTY

WWW.PLUMBLINK.CO.ZA

Plumblink tries its best to ensure that the information given on our website is accurate. Although, we cannot guarantee this for certain, and accept no liability for any information.

